

HAVILAND CONSUMER PRODUCTS, INC
SAFETY DATA SHEET



Section 1: Identification

Product Name: Ideal pH Reducer Product Code: C002600

Haviland Consumer Products, Inc.
421 Ann Street NW
Grand Rapids, MI 49504
(616) 361-6691

Emergency Phone
CHEMTREC (800) 424-9300
CHEMTREC International (703) 527-3887

Product Use: NA
Not recommended for: NA

Section 2: Hazard(s) Identification

GHS Ratings:

| | | |
|----------------|----|--|
| Skin corrosive | 1C | Destruction of dermal tissue: Exposure < 4 hours Observation < 14 days, visible necrosis in at least one animal |
| Eye corrosive | 1 | Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5 |

GHS Hazards

| | |
|------|---|
| H314 | Causes severe skin burns and eye damage |
| H318 | Causes serious eye damage |

GHS Precautions

| | |
|----------------|---|
| P260 | Do not breathe dust/fume/gas/mist/vapors/spray |
| P264 | Wash face, hands, and any exposed skin thoroughly after handling |
| P280 | Wear protective gloves/protective clothing/eye protection/face protection |
| P310 | Immediately call a POISON CENTER or doctor/physician |
| P321 | Specific treatment (see first aid treatment on SDS) |
| P363 | Wash contaminated clothing before reuse |
| P301+P330+P331 | IF SWALLOWED: Rinse mouth. Do NOT induce vomiting |
| P303+P361+P353 | IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower |
| P304+P340 | IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing |
| P405 | Store locked up |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulations |

Danger



Section 3: Composition/Information on Ingredients

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|---|----------------------|-----------------------|-----------------------|
| Sodium bisulfate 7681-38-1 90 to 100% | | | |

Section 4: First-aid Measures

Inhalation

Rescuers should put on appropriate protective gear. Remove from area of exposure. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Keep victim warm. Get immediate medical attention. To prevent aspiration, keep head below knees.

Eye Contact

Immediately flush eyes with water. Flush eyes with water for a minimum of 15 minutes, occasionally lifting and lowering upper lids. Get medical attention promptly.

Skin Contact

Remove contaminated clothing. Wash skin with soap and water. Get medical attention. Wash clothing separately and clean shoes before reuse.

Ingestion

If swallowed, do NOT induce vomiting. Give victim a glass of water. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Section 5: Fire-fighting Measures

LEL:

UEL:

Extinguishing Media

For fires in area use appropriate media. For example: Water spray. Dry chemical. Carbon dioxide. Foam.

Specific Hazards Arising from the Chemical

Fire and Explosion Hazards: Toxic fumes, gases or vapors may evolve on burning.

Hazardous Combustion Products: Toxic vapors. Sulfur oxides. Sulfur dioxide. Metal oxides. Sodium sulfide may be formed after dried solution residues are heated. This is an explosive hazard and strongly alkaline in contact with water.

Special Protective Equipment and Precautions for Firefighters

Special Information: As in any fire, wear self-contained breathing apparatus pressure-demand (MSHA/NIOSH approved or equivalent) and full protective gear.

Section 6: Accidental Release Measures

Spill Clean-Up Procedures: CORROSIVE MATERIAL. Evacuate unprotected personnel from area. Maintain adequate ventilation. Follow personal protective equipment recommendations found in Section 8. Never exceed any occupational exposure limit. Eliminate all sources of ignition. Shut off source of leak if safe to do so. Contain spill, place into drums for proper disposal. Neutralize with an alkali (sodium carbonate, lime, etc.) Sulfur dioxide and carbon dioxide may be released during neutralization. Flush remaining area with water to remove trace residue and dispose of properly. Avoid direct discharge to sewers and surface waters. Notify authorities if entry occurs.

Section 7: Handling and Storage

HANDLING: Use only in a well ventilated area. Avoid breathing vapor, fumes or mist. Avoid contact with eyes, skin, and clothing. Ground and bond containers when transferring material. Always open containers slowly to allow any excess pressure to vent. Follow all MSDS/label precautions even after containers are emptied because they may retain product residues.

STORAGE: Keep away from heat, sparks, and flame. Store containers in a cool, well ventilated place. Keep container closed when not in use. Protect from direct sunlight.

Section 8: Exposure Control/Personal Protection

| Chemical Name / CAS No. | OSHA Exposure Limits | ACGIH Exposure Limits | Other Exposure Limits |
|-------------------------------|----------------------|-----------------------|-----------------------|
| Sodium bisulfate 7681-38-1 | | | |

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant the use of a respirator.

SKIN PROTECTION: Wear impervious protective gloves. Wear protective gear as needed - apron, suit, boots.

EYE PROTECTION: Wear safety glasses with side shields (or goggles) and a face shield.

OTHER PROTECTIVE EQUIPMENT: Facilities storing or utilizing this material should be equipped with an eyewash facility and a safety shower.

HYGIENIC PRACTICES: Do not eat, drink, or smoke in areas where this material is used. Avoid breathing vapors. Remove contaminated clothing and wash before reuse. Wash thoroughly after handling. Wash hands before eating.

Section 9: Physical and Chemical Properties

| | |
|---|--|
| <p>Appearance: Off-white granular material</p> <p>Vapor Pressure: Unknown</p> <p>Vapor Density: Unknown</p> <p>Density: Unknown</p> <p>Freezing point: Unknown</p> <p>Boiling range: Unknown</p> <p>Evaporation rate: Unknown</p> <p>Explosive Limits: Unknown</p> <p>Autoignition temperature: Unknown</p> <p>Viscosity: Unknown</p> | <p>Odor: Fresh to pungent odor</p> <p>Odor threshold: Unknown</p> <p>pH: < 1 (5% solution)</p> <p>Melting point: 350°F (177°C)</p> <p>Solubility: 1080 g/l @ 68°F (20°C)</p> <p>Flash point: Unknown</p> <p>Flammability: Unknown</p> <p>Specific Gravity: Unknown</p> <p>Decomposition temperature: Unknown</p> <p>Grams VOC less water: Unknown</p> |
|---|--|

Section 10: Stability and Reactivity**Chemical Stability:**

STABLE

Incompatible Materials

Acids. Mineral acids. Oxidizing agents. Corrosive to some metals.

Conditions to Avoid

Avoid contact with heat, sparks, electric arcs, other hot surfaces, and open flames. Avoid other ignition sources. Temperatures at or near boiling point causes evolution of Sulfur dioxide. Avoid excess exposure to air. On exposure to air, the product will lose some Sulfur dioxide and gradually oxidize to sulfate.

Hazardous Decomposition Products

we can not guarantee that these are the only hazards which exist. Our SDS are based only on data available at the time of shipping and are subject to change without notice as new information is obtained. Avoid long storage periods since the product is subject to degradation with age and may become more dangerous or hazardous. It is the responsibility of the user to request updated SDS for products that are stored for extended periods. Disposal of unused product must be undertaken by qualified personnel who are knowledgeable in all applicable regulations and follow all pertinent safety precautions including the use of appropriate protective equipment (e.g. protective goggles, protective clothing, breathing equipment, face mask, fume hood). For proper handling and disposal, always comply with federal, state and local regulations.